

[Web](#) [Images](#) [Maps](#) [News](#) [Shopping](#) [Gmail](#) [more ▾](#)[Sign in](#)

superimpose first search condition setting sec

[Search Patents](#)[Advanced Patent Search](#)  
[Google Patent Search](#)

Filing date

☐ Return patents filed anytime☒ Return patents filed between Jan ▾ 1980 ▾ and Dec ▾ 1999 ▾

Patents

Showing: Any status ▾View as: List ▾

Patents 1 - 10 on superimpose first

[Sort by relevance](#) | [Sort by date \(new first\)](#) | [Sort by date \(old first\)](#)

### Traffic surveillance system

US Pat. 6466260 - Filed Nov 12, 1998 - Hitachi Denshi Kabushiki Kaisha

In 30 this case, since the VTR 52 continuously records a video signal, the video signal need ... and a second controller, coupled to said first controller, ...

### Video camera system which multiplexes internal, external, and sensing ...

US Pat. 5581362 - Filed Jul 29, 1994 - Matsushita Electric Industrial Co., Ltd.

However, it is difficult to search for and find a frame representative of the content ... 1 is a block diagram of a video camera system according to a first ...

### Image data supervising system

US Pat. 5130813 - Filed Aug 28, 1989 - Casio Computer Co., Ltd.

Then, under this photo- 25 graphing condition, when the register key 228 is ... by said second output means on said image signal reproduced by said first ...

### Supplemental audio visual emergency reviewing apparatus and method

US Pat. 5842978 - Filed Nov 18, 1996

The RF receiver 26 at a second location remote from the first location of ... Fifth and finally, the video monitor 18 receives the audio output signal and ...

### Still image filing system

US Pat. 5261048 - Filed Apr 12, 1990 - Sony Corporation

Further, the video bus and the first and second control buses are provided in ... thereby the control data superimposed upon the video signal being supplied ...

### Multiple beam high definition page display

US Pat. 4633244 - Filed Sep 30, 1983 - Honeywell Information Systems Inc.

A storage or memory is required in a 60 system employing a non-memory CRT because the video signal must be applied to the CRT a number of times a second. ...

### Multiple beam high definition page display

US Pat. 4616160 - Filed Jul 29, 1985 - Honeywell Information Systems Inc.

A storage or memory is required in a system employing a non-memory CRT because the video signal must be applied to the CRT a number of 65 times a second. ...

### Knowledge base system and recognition system

US Pat. 5748850 - Filed Jun 5, 1995 - Hitachi, Ltd.

20 Additionally, using a video signal as the input to the At a point where ... engine including procedures in search has already been conducted for all ...

### Sync signal separator apparatus

US Pat. 5995157 - Filed Feb 2, 1998 - Oren Semiconductor Ltd.

For a better understanding and by way of example only, after having executed the first and second stages a synchronization with the V sync signal (250) at a ...

Ergonomic man-machine interface incorporating adaptive pattern recognition ...

US Pat. 6081750 - Filed Jun 6, 1995

The search is first conducted for an operator in a parameter space of operators, 14 Brady, ... Its Fractal compression methods may be used for video data 45 ...

Stay up to date on these results using [the patents RSS feed on superimpose first search condition setting second video signal](#).

Google ►

Result Page: 1 2 [Next](#)

superimpose first search condition setting sec [Search Patents](#)

[Google Patent Search Help](#) | [Advanced Patent Search](#)

[Google Home](#) - [About Google](#) - [About Google Patent Search](#)

©2008 Google

Web Images Maps News Shopping Gmail more ▾

Sign in



superimpose first search condition setting sec

Search Patents

Advanced Patent Search  
Google Patent Search

Filing date ☐ Return patents filed anytime

☒ Return patents filed between Jan ▾ 1980 ▾ and Dec ▾ 1999 ▾

Patents

Showing: Any status ▾

View as: List ▾

Patents 11 - 18 on superimpose fir

Sort by relevance | Sort by date (new first) | Sort by date (old first)

### Video processing circuit

US Pat. 6538703 - Filed Mar 26, 1999 - Funai Electric Co., Ltd.

Sato et al Bae et al Sparks Park Ryu A video processing circuit for ... a first or second input terminal and for outputting the video signal as it is ...

### CCD based particle image direction and zero velocity resolver

US Pat. 5491642 - Filed Dec 3, 1993 - United Technologies Corporation

In each sub-region the first exposure particles are again shown by the hollow dots 84 and the second exposure particles by the solid dots 86. ...

### Television receiver with a dual tuner system

US Pat. 5285284 - Filed Nov 9, 1992 - Kabushiki Kaisha Toshiba

EXTERNAL VIDEO INPUT 25 SUB PICTURE CONVERTING CIRCUIT PIP ON/OFF CONTROL ...

[57] ABSTRACT A television receiver having first and second tuners which can ...

### Reproducing apparatus using pilot signal crosstalk for tracking control and ...

US Pat. 6005741 - Filed Nov 18, 1996 - Canon Kabushiki Kaisha

REPRODUCED VIDEO SIGNAL ) REPRODUCED AUDIO SIGNAL ... superimposed in a first area thereof, and the pilot signal is superimposed in the second area of the ...

### Video recording camera

US Pat. 4764817 - Filed Jun 10, 1987 - Leonard Bloom

An electronic viewfinder of the type used in the video recording camera is ... in the audio signal level of outputs from the microphones 31, 32), a second ...

### Cathode ray tube (CRT) having shaped beams

US Pat. 4603279 - Filed Sep 30, 1983 - Honeywell Information Systems Inc.

A storage or memory is required in a system employing a non-memory CRT because the video signal must be applied to the CRT a number of times a second. ...

### [APPLICATION] DISPLAY SYSTEM

US Pat. 9247815 - Filed Feb 9, 1999


2, because it would be necessary to connect three each signal lines (R, ... to another search range 0 to meters, the key 116 is first pressed down so ...

### CATV subscriber disconnect switch

US Pat. 5323462 - Filed Nov 12, 1992 - Scientific-Atlanta, Inc.

The control signal toggles a program denial device between first and second conditions. The program denial device, responsive to the control signal waveform ...

Stay up to date on these results using the [patents RSS feed on superimpose first search condition setting second video signal](#).



Result Page: [Previous](#) [1](#) [2](#)

[Google Patent Search Help](#) | [Advanced Patent Search](#)

[Google Home](#) - [About Google](#) - [About Google Patent Search](#)

©2008 Google